



Home/Office Security System 16 Channel Digital Video Recorder With Motion Detection and Audio



- Motion trigger recording function
- Support 2 removable HDDs (over 250GB), IDE type
- Wavelet Compression Format replaces Time Lapse VCR + Multiplexer
- Stand-alone design
- 4 Level video quality adjustable: Best / High / Normal / Basic
- Support 4 / 7 / 9 / 10 / 13 / 16 Channels Multiplexing function
- 16 Channels alarm input, one alarm output and ALARM display
- Video loss detected in each channel can record up to 160 events
- Power-loss memory function
- · Quick Multiple Search by date / time, alarm and full list
- Security password protection
- RS-232 and RS-485 communication protocol

www.swannsecurity.com

Enquiries: info@swann.com.au Product Code: SW-R-DVR16



Home/Office Security System 16 Channel Digital Video Recorder With Motion Detection and Audio

16 Ch Digital Multiplex recorder, is a device which uses digital technology to manage video image in HDD. It includes features such as timer setting for searching, nice recording quality, fast / slow forward, reverse search and user-friendly operations. It is the best device to replace Time Lapse VCR + 16 Ch Multiplexer and the best unit to cover 4 Ch to 16 Ch DVR Installation.



Color/ Contrast/

Brightness Adjustable

TTL input, Hi (5V),

RS-232 or RS-485

 \pm 10% switching adaptor

AC100~240V

Low (GND) COM,/N.O.

Technical Specifications

Video format: Hard disk storage:

Camera Input Signal & Loop Back:

Main & Call Monitor Output:

Audio input: Audio output: Motion Detect Area:

Video Loss Detection: Refresh Rate:

Recording Rate:

Picture in Picture: Key Lock: Picture Zoom: NTSC/EIA or PAL/CCIR IDE type, UDMA 66, supported over 250GB HDD

Composite video signal I Vp-p 750 BNC, 16 channels

Composite video signal I Vp-p 75O BNC 4 audio inputs, (RCA) 2 audio outputs, (RCA) I 5 * I 2 targets per camera (NTSC) / I 5 * I 4 targets per camera (PAL) Yes Up to I 20 fields/sec. for NTSC / I 00 fields/sec. for PAL Up to 25 images/sec. for NTSC / I 8 images/sec. for PAL Yes (Movable) Yes 2*2 (Movable)

Video Adjustable:

Alarm Input:

Alarm Output: Remote Control: Power Source:

 Power Consumption:
 <45W</td>

 Operation Temperature:
 10 ~ 40°C

 RS-232C / RS-485 (bps) | 15200, 57600, 19200,

 9600, 4800, 3600, 2400, 1200

 Dimension:
 (mm) 432(W) x 110(H)

 x 325(D)

Net Weight:

Package Contents

DVR Power Adaptor Power Cable Instructional Manual (Manual only available in English)

5.7 kgs





Please note that the information contained within this document is subject to change without notification.